



TECHNICAL DATA SHEET

SUPER LUBE® CYCLE LUBE SYNTHETIC LUBRICANT WITH SYNCOLON® (AEROSOL)

March 2024

PRODUCT DESCRIPTION:

Super Lube® Cycle Lube Synthetic Lubricant with Syncon® (Aerosol) is a synthetic multi-purpose grease especially designed for bicycle and motorcycle applications. Ideal for long-lasting lubrication in all weather conditions. This formula is fortified with Syncon® with anti-wear, anti-corrosion and extreme pressure additives that provide long lasting lubrication.

Super Lube® Cycle Lube Aerosol cleans and penetrates, then dries to leave a water-repelling grease film that protects. Spray it on chain, derailleur, brake and shifter points, pivoting points and other moving parts.



FEATURES:

- ❖ Dielectric
- ❖ Food Grade
- ❖ Clean
- ❖ Prevents rust and corrosion while reducing friction
- ❖ Provides superior anti-wear performance
- ❖ Penetrates and coats
- ❖ Will not drip, run or evaporate
- ❖ Longer chain life, reduces maintenance
- ❖ Remains free flowing in freezing temperatures
- ❖ Water and salt water resistant
- ❖ Kosher certified

TYPICAL APPLICATIONS:

For use on motorcycles and bicycles:

- ❖ Chain lubrication
- ❖ Pivot points and derailleurs
- ❖ Front and rear brakes
- ❖ Shifter points and cables

PACKAGE SIZES:

Part No.	Description
33006	6 oz. Aerosol



TECHNICAL DATA SHEET

SUPER LUBE® CYCLE LUBE SYNTHETIC LUBRICANT WITH
SYNCOLON® (AEROSOL)

March 2024

PROPERTIES:

Test	Rating
NLGI Grade (Base):	2
Color:	Translucent
Temperature range:	-45°F to 450°F
Specific gravity:	.866
Odor:	Solvent-like
Type of film:	Non-drying
Solvent content VOC (California):	<25%

DIRECTIONS:

- Using a chain cleaning tool or old toothbrush, clean chain links, use mineral spirits if necessary.
- Dry the chain.
- Shake aerosol well before using. Use handy extension tube for pinpoint applications.
- Spray the entire chain.
- Re-apply as necessary.

SHELF LIFE / WARRANTY:

Super Lube® products have a five (5) year recommended shelf life when stored in the original container and in reasonable ambient conditions. The warranty period is twenty-four (24) months from the date of purchase. For complete information visit www.super-lube.com/what-is-the-shelf-life-ezp-320.html.



See Safety Data Sheet (SDS)
for further detail regarding
safe use of this product.



Made in USA

The information provided in this Technical Data Sheet including the recommendations for use and application of the product are based on our knowledge and experience of the product as of the date of this bulletin. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Kano Laboratories LLC is, therefore not liable for the suitability of our product for the production processes and conditions in respect for which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

All Super Lube® and Syncolon® trademarks in this document are trademarks of Kano Laboratories LLC.