

## TECHNICAL DATA SHEET

### SUPER LUBE® SILICONE LUBRICANT NON-AEROSOL PUMP

March 2024

#### PRODUCT DESCRIPTION:

Super Lube® Silicone Lubricant Non-Aerosol Pump was developed because of environmental concerns. Many industrial facilities do not allow the use of aerosol products. This product addresses these needs.

Super Lube® Silicone Lubricant Non-Aerosol Pump is a general-purpose lubricant, primarily designed to reduce friction in non-load bearing assemblies and is safe to use on rubber, plastic, and vinyl.

The silicone base has high dielectric capabilities and protects well against rust and corrosion.

Super Lube® Silicone Lubricant Non-Aerosol Pump is NSF Food Grade rated H1 for incidental food contact. Meets former USDA (H1) guidelines.



#### FEATURES:

- ❖ Corrosion inhibitor
- ❖ Long lasting
- ❖ Safe to use on rubber, vinyl and plastic
- ❖ Dielectric
- ❖ Prevents freezing
- ❖ Extreme temperature use
- ❖ Prevents doors, locks and windows from binding and squeaking
- ❖ Kosher certified
- ❖ NSF Registered H1, # 136589

#### TYPICAL APPLICATIONS:

- ❖ O-rings, rubber gaskets and grommets
- ❖ Doors, locks and windows
- ❖ Food manufacturing equipment
- ❖ Tools
- ❖ Mold release
- ❖ High speed machinery
- ❖ Electronic equipment
- ❖ Weather stripping
- ❖ Treadmills
- ❖ Exercise equipment



## TECHNICAL DATA SHEET

### SUPER LUBE® SILICONE LUBRICANT NON-AEROSOL PUMP

March 2024

#### PACKAGE SIZES:

Part No.	Description
56132	1 Quart Bottle with Trigger Sprayer

#### PROPERTIES:

Test	Test Method	Rating
Color:		Translucent clear
Temperature Range:		-58°F to 392°F (-50°C to 200°C)
Flashpoint:	ASTM 92	>300°C
Type of film:		Non-drying
Specific gravity:	ASTM 1298	.965

#### DIRECTIONS:

- Wipe areas to be treated.
- Apply enough lubricant to coat all areas of contact.
- Reapply as needed.

#### SHELF LIFE / WARRANTY:

Super Lube® products have a five (5) year recommended shelf life when stored in the original container and in reasonable ambient conditions. The warranty period is twenty-four (24) months from the date of purchase. For complete information visit [www.super-lube.com/what-is-the-shelf-life-ezp-320.html](http://www.super-lube.com/what-is-the-shelf-life-ezp-320.html).



See Safety Data Sheet (SDS) for further details regarding safe use of this product.



The information provided in this Technical Data Sheet, including the recommendations for use and application of the product are based on our knowledge and experience of the product as of the date of this data sheet. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Kano Laboratories LLC is, therefore not liable for the suitability of our product for the production processes and conditions in respect for which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

All Super Lube® trademarks in this document are trademarks of Kano Laboratories LLC.