

Super Lube® "...everywhere and no wear"!



Kano Laboratories LLC
24 DaVinci Drive, PO Box 405
Bohemia, NY 11716-0405
Phone (631) 567-5300, Fax (631) 567-5359
e-mail: info@super-lube.com
www.super-lube.com

COMPATIBILITY CHART

Super Lube® SuperPull Electrical Fiber Optic Pulling Compound

Polymer (plastics) Constant Strain Tensile Testing	Rating
Acrylonitrile Butadiene Styrene (ABS)	E
Cellulose acetate (CA)	E
Polyamide (PA) (Nylon)	E
Polycarbonate (PC)	E
Polyethylene (PE)	E
*ultra high molecular mass (PE-UHMW)	E
*low density (PE-LD)	E
Polyethylene-/polybutylenetherephthalat (PET / PBT)	E
Polyoxymethylene, Polyacetate (POM) (Delrin)	E
Polypropylene (PP)	E
Polyphenylene oxide (PPO)	E
Polyphenylene sulphide (PPS)	E
Polystyrene (PS)	E
Polytetrafluoroethylene (PTFE)	E
Polyurethane (PUR)	E
Polyvinylchloride (PVC)	E
Thermoplastic elastomer (TPE)	E
Very Low Density Polyethylene (VLDPE)	E
Electrical Metal Tubing (EMT) (Metal)	E
Elastomer (rubber)	Rating
Acrylic rubber (ACM)	E
Buna S	E
Butyl (IIR)	E
Chlorosulfonated Polyethylene (CSPE)	E
Ethylene-propylene-diene rubber (EPDM)	E
Ethylene Propylene Rubber (EPR)	E
Natural rubber (NR)	E
Neoprene	E
Nitrile (NBR)	E
Polyurethane (AU, EU)	E
Styrene-butadiene rubber (SBR)	E
Viton (FKM)	E
RATING KEY	
E - Compatibility Excellent	
G - Compatibility Good	
NC - Not Compatible	